



DOP DREDGER 350L

PICTURE OF SIMILAR VESSEL

GENERAL

Type	DD 350L
Basic functions	Capital mining and maintenance dredging

DREDGING FEATURES

Max. dredging depths	-50 m / -100 m
Max. mixture capacity	2,400 m ³ /h
Max. total head	3.2 bar

DREDGE INSTALLATION

Dredge pump type	BP3530LD
Max. power at pump shaft	240 kW
Diameter suction/discharge pipe	350 mm
Spherical passage pump	200 mm
Sand production head	Included with jet water nozzles

JET WATER PACK

Jet water pack capacity	600 m ³ /h
Jet water pack pressure	8 bar

HYDRAULIC POWER PACK

Hydraulic flow max.	738 L/min
Hydraulic pressure max.	275 bar
Hydraulic installation	Driving DOP350L and winches

PRINCIPAL DIMENSIONS

Length o.a.	20.70 m
Length over pontoons	11.70 m
Beam o.a.	7.35 m
Depth	1.80 m
Draught	1.30 m
Air draught	8.10 m
Total weight	48 tons

TANK CAPACITIES

Fuel oil approx.	5.00 m ³
------------------	---------------------

DECK MACHINERY

Hoisting winch	Hydraulic, 80 kN, 0-15 m/min
Maneuvering winches (3x)	Hydraulic, 50 kN, 0-15 m/min

INSTRUMENTATION

Dredging depth indicator
 Pressure indication of dredge pump
 RPM indication of dredge pump

REMARKABLE FEATURES

Dismountable design which allows transport by road
 Spacious ergonomic designed control cabin
 One operator can control the entire dredger from the control cabin
 Transportable in standard Open Top Containers

DOP DREDGER 350L



DAMEN

DAMEN SHIPYARDS GROUP

Avelingen-West 20
4202 MS Gorinchem
The Netherlands

P.O. Box 1
4200 AA Gorinchem
The Netherlands

phone +31 (0)183 63 99 22
fax +31 (0)183 63 21 89

info@damen.com
www.damen.com

© No part of the leaflet may be reproduced in any form, by print, photo print, microfilm, or any other means, without written permission from Damen Shipyards Group